

INVITATION TO BID

(This is not an order.)

Buyer: Gregory Hart 216-664-7076 ghart@clevelandohio.gov

CITY OF CLEVELAND Division of Purchases & Supplies

601 Lakeside Avenue Room 128 Cleveland, OH 44114 Requestor: Lavelle Gibson 216-898-5160 lgibson@clevelandairport.com

	Event Description Department/Division Public Bid Opening Date/Time July 16, 2025 3:00 PM 3001 July 16, 2025 3:00 PM SCHEDULE OF EVENTS Event Description Event Date Group/ Commodity Description Item Quantity/ Service Catalog 1/1 ForkLift Item Quantity/ Service Catalog Discount 1/1 ForkLift Spees. From To To Discount (J)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Overall Loader Height - 85.20 Over Head Guard Height - 80.20 Over Head Guard Height - 80.20 Over Head Guard Height - 85.20 Over Head Guard Height - 80.20 Over Head Guard	Procuremen	t Folder	RFB No.	RFB Description			
Image: Section of the sectis of the section of the section of the section of the	Section 3001 July 16, 2025 3:00 PM Source Event Description Event Description Event Date Group/ Line# Event Description Event Date Group/ Line# Event Description Event Date Group/ Line# Event Description Event Date Open Colspan="2">Colspan="2">Colspan="2">Catalog Discount 1 / 1 ForkLift Service Catalog Discount To To To ForkLift Specs. (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tight - 187.0 Over Head Guard Height - 187.0 Carlaige Forks 48" x 5" x 1.8" - Class III Line # Theo Type 4"" carraiage <td colspa="</th"><th>54245</th><th></th><th>RFB 3001 20250000000333</th><th>Forklift</th><th></th><th></th></td>	<th>54245</th> <th></th> <th>RFB 3001 20250000000333</th> <th>Forklift</th> <th></th> <th></th>	54245		RFB 3001 20250000000333	Forklift		
Event Description Event Date Group/ Line# Commodity Description Item Quantity/ UOM Dates 1/1 ForkLift From To To ForkLift Spees. (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Over Head Guard Height - 89.2 Over Head Guard Height - 89.2 Over Head Guard Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4V-US Industrial LP Engine Engine 2.1L 4V-US Industrial LP Engine Engine 3.1 (@ 2570 rpm SAE H-P) Net Horsepower Rating: 51 (@ 2570 rpm SAE HP) Transmission Automatic Transmission	SCHEDULE OF EVENTS Event Description Event Date Group/ Line# Commodity Description Item Quantity/ UOM Dates 1/1 ForkLift From To Discount 1/1 ForkLift From To To	RFB Closing	g Date/Time		Department/Division	Public Bid Opening	Date/Time	
Event Description Event Date Group/ Line# Commodity Description Item Quantity/ UOM Service Dates Catal Discord 1 / 1 ForkLift From To From To From To Item Quantity/ Dates Discord 1 / 1 ForkLift From To From Item Quantity/ Dates Discord 1 / 1 ForkLift Specs. ForkLift Specs From To Item Quantity/ Dates Discord (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Masti Specifications: Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Over Head Guard Height - 85.50 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Item Capacity Base Model Capacity 6,000 lbs. Event Past Past Past Past Past Past Past Pas	Event Description Event Date Group/ Line# Commodity Description Item Quantity/ UOM Service Dates Catalog Discount 1/1 ForkLift From To From To From To Service Catalog 1/1 ForkLift Specs. ForkLift Specs. From To To Service Catalog (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Service Lifting Capacity, based on quoted specifications - 5,750 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Service Service and and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks- longer than 96", consult Cascade) Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2 Lift - U4-U5 Industrial LP Engine I36 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Horsepower Rating; 112 @ 1800 rpm SAE HP Transmission Automatic Transmission Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels	uly 16, 2025	3:00 PM		3001	July 16, 202	25 3:00 PM	
Group/ Line# Commodity Description Item Quantity/ UOM Service Dates Catal- Discort 1/1 ForkLift From To Ford To From To From To ForkLift Specs. (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine Engine 21.2. 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission 21800 rpm SAE HP Transmission 21800 rpm SAE HP	Group/ Line# Commodity Description Item Quantity/ UOM Service Dates Catalog Discount 1 / 1 ForkLift Ford From To Ford Discount 1 / 1 ForkLift From To Ford Discount Discount 1 / 1 ForkLift Ford To Discount Discount 1 / 1 ForkLift Ford Ford Discount Discount Discount 1 / 10 State Ford Ford Discount Discount Discount 1 / 10 Maximum Fork Height - 187.0 Discount	SCHEDULE	OF EVENTS					
Line# UOM Dates Discord 1/1 ForkLift From To From To From To ForkLift Specs. (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Overal Lowered Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage TrA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 112 @ 1800 rpm SAE HP Transmission Automatic Transmission	Line# UOM Dates Discount 1/1 ForkLift From To ForkLift From To Image: Construction of the second of t			Event Description		Event Date		
To ForkLift Specs. (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Horsepower Rating: 51 @ 2570 rpm SAE fl-lb Net Horsepower Rating: 51 @ 2570 rpm SAE fl-Pb Net Horsepower Rating: 51 @ 2570 rpm SAE fl-Pb Transmission Automatic Transmission	To ForkLift Specs. (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.3" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)		C	Commodity Description				
 (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HIP Transmission Automatic Transmission 	 (1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 47-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic) 	1 / 1	ForkLift					
tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	tips, while providing smooth, quiet and consistent operation. Mast Specifications: Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)	ForkLift Sp	ecs.					
Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Maximum Fork Height - 187.0 Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)				t visibility to load and fork			
Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Overall Lowered Height - 89.2 Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires: 28x9-15-12PR (Pneumatic)							
Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Over Head Guard Height - 85.50 Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Free Lift - 41.2" with standard Load Backrest Lifting Capacity Base Model Capacity 6,000 lbs. @24 load center Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Actual Capacity, based on quoted specifications - 5,750 lbs. @24 load center to 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission 	 187.0 MFH Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic) 							
Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Tilt 6 degrees forward and 6 degrees backwards Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)	1	· · · ·	oted specifications - 5,750 lbs. @24	load center to			
Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Carriage ITA Hook Type 42" Carriage Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)			1 1 1 1				
Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Forks 48" x 5" x 1.8" - Class III Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Load Backrest 48" High Load Backrest Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade) Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm Engine 2.2L 4Y-US Industrial LP Engine 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)				Maximum 96" Forks- longer	than 96", consult Cascad	e)	
136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	 136 cubic inch displacement, 4-cylinder, overhead valve (OHV) Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic) 						· ·	
Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Net Torque Rating: 112 @ 1800 rpm SAE ft-lb Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission	Net Horsepower Rating: 51 @ 2570 rpm SAE HP Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
Transmission Automatic Transmission	Transmission Automatic Transmission Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
	Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)							
Steering Loud Sensing Hydrostatie Fower Steering with The Steering Column	Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)				ring Column			
Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)								
		Additional	Equipment Includ	led				
Additional Equipment Included	Additional Equipment Included							
Additional Equipment Included Int SSFP w 3&4 funct, hose				LP" (tank not included)				
Int SSFP w 3&4 funct. hose	Int SSFP w 3&4 funct. hose	Synchroniz	ed Steering					
Int SSFP w 3&4 funct. hose UL Approved Model Type "LP" (tank not included) Synchronized Steering	Int SSFP w 3&4 funct. hose UL Approved Model Type "LP" (tank not included) Synchronized Steering							
Int SSFP w 3&4 funct. hose UL Approved Model Type "LP" (tank not included) Synchronized Steering Steel Cabin (With Doors)	Int SSFP w 3&4 funct. hose UL Approved Model Type "LP" (tank not included) Synchronized Steering Steel Cabin (With Doors)							
Int SSFP w 3&4 funct. hose UL Approved Model Type "LP" (tank not included) Synchronized Steering Steel Cabin (With Doors) Rear View Mirrors (Left & Right Sides)	Int SSFP w 3&4 funct. hose UL Approved Model Type "LP" (tank not included) Synchronized Steering Steel Cabin (With Doors) Rear View Mirrors (Left & Right Sides)	Adjustable	Volume Back-up	<mark>Alarm (Sm</mark> art Alarm)				

Seatbelt Interlock Fire Extinguisher



INVITATION TO BID

(This is not an order.)

Buyer: Gregory Hart 216-664-7076 ghart@clevelandohio.gov

Requestor: Lavelle Gibson 216-898-5160 lgibson@clevelandairport.com

CITY OF CLEVELAND

Division of Purchases & Supplies 601 Lakeside Avenue Room 128 Cleveland, OH 44114

Procurement Folder RFB No. RFB Description			RFB Description						
154245 RFB 3001 20250000000333 Forklift									
RFB Closing Date/Tin	ne			Department/Division	Public Bid	Public Bid Opening Date/Time		te/Time	
July 16, 2025 3:00 PM				3001		July 16, 20	025 3	:00 PM	
	nber) on Light n Lights OFF) hts ON/OF Tires -								
All quantities are appro	oximate	and the order if any, shall not e	exceed	\$46,464.00 or one (1) yea	r whichever o	ccurs first	•		
Ship To: Vendor Response									
CHIA CENTRAL RE CHIA CENTRAL RE 19451 FIVE POINTS Cleveland, OH 4413	CEIVIN S RD			\$	Contract Am	ount			
Vendor Response	Vend	or Total Amount for Items	V	endor Total Amount for	Services	Payn	nent l	Discount	Offer
\$			\$				%		Day(s)
TERMS OF DELIVER	RY								
• Price quoted shall be	F.O.B. d	elivered to the place designated of	on purc	hase order. No other term	will be accept	able.			
 All charges for shippi specified dollar amou 	ing must nt inclus	d in terms of work days after rec be included within the Unit Pric sive of all shipping charges. sidered nor processed for payme	e for ea	ch item quote unless other	-				
BIDDER AGREES TO	о сом	PLY WITH ALL TERMS AN		DITIONS BELOW AN	D ON REVE	RSE SIDI	E OF	THIS BI	D
OTHERWISE DESI ALL SHIPPING CH NO FREIGHT CHA	R SHII GNAT ARGE RGES	PPING MUST BE INCLUD ED BY A SEPARATE LINE S. WILL BE CONSIDERED N MITTED PRIOR TO BID AV	E ITEN	4 WITH A SPECIFIED ROCESSED FOR PAY	DOLLAR A	MOUN	T INO	CLUSIVI	
	s all que	estions to the Buyer (See Ab	ove.) I	Do NOT contact the "R	equestor." Co	ontract on	ıly th	e Buyer l	isted



INVITATION TO BID

(This is not an order.)

Buyer: Gregory Hart 216-664-7076 ghart@clevelandohio.gov

CITY OF CLEVELAND

Division of Purchases & Supplies 601 Lakeside Avenue Room 128 Cleveland, OH 44114 Requestor: Lavelle Gibson 216-898-5160 lgibson@clevelandairport.com

Procurement Folder	RFB No.	RFB Description	
154245	RFB 3001 20250000000333	Forklift	
RFB Closing Date/Time		Department/Division	Public Bid Opening Date/Time
July 16, 2025 3:00 PM		3001	July 16, 2025 3:00 PM
BIDDER AGREES TO CON	IPLY WITH ALL TERMS AND CO	INDITIONS BELOW AND	ON REVERSE SIDE OF THIS BID
No Price increase			
This Purchase Order does n	not permit price increases.		
completeness of any and all in advance of the bid openin protest of award. Contact	ng date of any possible discrepancy the Buyer immediately if there is a	tial bidder does not notify then any such discrepan	id submission, the accuracy and the Division of Purchases and Supplies cy or erratum cannot be the basis for a ompleteness in these bid documents.
BIDDER MUST COMPLET	E & SIGN BELOW		
NAME OF THE FIRM:			
STREET ADDRESS:			
CITY:		STATE:	ZIP CODE:
FED ID # / SSN #:			
PHONE NO.:		FAX NO.:	
EMAIL ADDRESS:			
PLEASE PRINT CONTACT N	AME:		
AUTHORIZED SIGNATURE:		DATE:	
All bids and related document	ts must be enclosed in a sealed envelo	pe and marked with the RF	B number.
RETURN BID TO: Division o 601 Lakes Room 128 Cleveland	ide Ave		

Effective Immediately: In accordance with Codified Ordinance 181.13 (I) the City shall receive competitive sealed bids through email. All City of Cleveland bids estimated to be less than 50K in value will be submitted and received electronically via email. All bids must be emailed to CityofClevelandbids@clevelandohio.gov. Upon receipt of your bid, you will receive a reply indicating your bid has been received.

Bidder's Instructions

See enclosed <u>Terms & Conditions.</u> Read and follow all terms and conditions of the bid.

Bids must be submitted to CityofClevelandbids@clevelandohio.gov, the Document ID Number and Buyer's Name must be identified in the email subject line. Also clearly state the Document ID Number, Bid Description, Buyer's Name and Closing Date.

Bids received after the Closing Date, Closing Time and sent to any other email address not identified in the Bidders Instruction cannot be considered.

Northern Ireland Affidavit must be completed, signed and included with each bid.

The bid must be submitted to: CityofClevelandbids@Clevelandohio.Gov

Bids received after the Closing Date, Closing Time and sent to any other email address not identified in the Bidders Instruction cannot be considered.

The bid documents must include:

□ The Document ID Number and Buyers Name in email subject line
 □ PDF File of Request For Bid Form
 □ Terms & Conditions.
 □ Northern Ireland Affidavit.

Contact the Buyer immediately at the number on the Bid Form if you do not have all the required documents.

TERMS AND CONDITIONS

- 1. <u>Acceptance of Purchase Order.</u> This Purchase Order shall be effective when Seller executes it, otherwise indicates its acceptance, or delivers to the City of Cleveland any of the goods ordered herein or renders for the City any of the services ordered herein. If this Purchase Order has been issued by the City in response to an offer, then the issuance of this Purchase Order by the City shall constitute an acceptance of such offer subject to the express condition that the Seller assent to any additional or different terms contained herein. Any additional or different terms or conditions contained in any acknowledgement of the purchase by the Seller shall automatically be deemed objected to by the City and shall not be binding upon the City unless specifically accepted by the City in writing.
- 2. <u>Entire Agreement.</u> This order, the instructions to bidders, the Request for Bid, the Bid Schedule of Items, and any specification and/or other attachments, if any, incorporated hereby by reference, constitute the entire agreement between the parties and replaces and supersedes any prior or contemporaneous communications, representations, or agreements, whether oral or written with respect to such matter.
- 3. Indemnification. Seller shall indemnify, defend, and hold harmless the City, its officers, agents, and employees from all claims, demands, liabilities, losses, suits, cause of action, judgments, costs, and expenses, including attorneys' fees, arising, occurring, or allegedly arising or occurring from the personal injury, including death, property damage, including loss of use, or otherwise, to any person or the property of any person, including third parties and employees of any party, as a result of negligent or intentional act or omission of Seller or its agents, employees, subSellers or suppliers, in the furnishing of the goods covered by this PO, or because of any imperfection or defect in said goods, or based upon any claim of product liability of strict liability in tort, or because of the failure of such goods to be in accordance with the description of such goods as may appear in any catalog, analytical information report or other technical bulletin as is furnished or used by the City, or because of the failure of such goods to be produced in compliance with the requirements of this PO.
- 4. Limit of Liability. In no event shall the City be liable for anticipated profits, incidental or consequential damages, or penalties of any description. The City's liability on any claim arising out of or connected with or resulting from this contract or from the performance or breach thereof shall in no case exceed the price allocable to the goods or services or unit thereof which gives rise to the claim.
- 5. <u>Remedies.</u> The city's remedies shall be cumulative and remedies herein specified do not exclude any remedies allowed by law or in equity. Waiver of any breach shall not constitute waiver of any other breach of the same or any other provision. Acceptance of any items or payment therefore shall not waive any breach.
- 6. Default. Payment or acceptance of any items after the delivery date shall not constitute a waiver of the City's right to cancel this order with respect to subsequent deliveries. The City reserves the right to reasonable testing and inspection before payment or acceptance. The City's failure to inspect and accept or reject goods, materials, or articles shall not relieve Seller from liability for tender or delivery of nonconforming goods nor constitute a waiver of any of the City's rights or remedies for breach of contract. The City reserves the right to reject any or all items not in conformity with the specifications noted within this purchase order in any respect.
- 7. F.O.B. Destination. Freight terms are F.O.B. Destination, Freight Prepaid, unless otherwise approved in writing by the Commissioner of Purchases and Supplies.
- 8. Non-Assignment, Neither this contract, nor any interest herein, shall be assigned or subcontracted by the Seller except upon the prior written consent of the City.
- 9. <u>Patent, Trademark or Copyright Infringement.</u> Seller agrees to defend, entirely at its own expense, all claims, demands, and actions that may be asserted against the City for all alleged patent, trademark, and/or copyright infringement resulting from the use or resale of goods covered by the PO, and to indemnify and hold the City harmless against all costs, expenses, legal fees, and judgments related to such claims, demands, and actions.
- 10. <u>Timing</u>. Time is of the essence in this contract. Failure to deliver within the time specified shall entitle the City, in addition to any other rights or remedies, to cancel this order and purchase the goods elsewhere, in which event the Seller shall be responsible for any increase in cost.
- 11. <u>Implied Warranty</u>. In addition to its standard warranty, Seller warrants that all goods supplied will be free and clear of all liens and encumbrances, good and merchantable title being in the Seller. Upon receipt by Seller of payment, good and merchantable title will vest in the City. All goods will be free from any defects in design, materials or workmanship and will be of good and merchantable quality. All goods will conform to the City's specifications or the approved sample as the case may be, and will be fit for the known purposes for which purchased, and that Seller will not substitute
 - anything without the City's written consent.
- 12. Change Orders, No changes in the PO, its prices, terms, conditions, length, or attachments are permitted, without the City's prior written approval.
- 13. <u>Cancellation</u>. The City shall have the right to cancel this order, or any undelivered portion of this order, without cause, and its liability for such cancellation shall be limited to Seller's actual cost for work and materials applicable solely to this order that have been expected when Seller receives notice of cancellation. The City may, at its option, cancel this order without liability to Seller (except for conforming shipments the City previously accepted) if Seller (a) ceases to exist, (b) becomes insolvent, (c) becomes the subject of bankruptcy or insolvency proceedings, or (d) commits a breach in the performance of any obligation under this agreement or of any other written agreement with the City of Cleveland.
- 14. <u>Compliance with Laws</u>. Seller shall comply with all federal, state, and local laws, ordinances, rules, and regulations in the manufacture and sale of the goods and performance of the services. Seller shall defend and hold the City harmless from any losses, damages, or costs arising from or caused in any way by Seller's actual or alleged violation of any federal, state, or local law, ordinance, rule or regulation.
- 15. Access to Records: Seller shall provide access to pertinent records relative to this contract/order for a period of three (3) years after the last receipt of payment is made under this contract/order, whichever occurs last.
- 16. <u>Material Safety Data Sheets:</u> Any substance delivered as a part of this order must be properly labeled in accordance with all applicable regulations and must be accompanied by a Material Safety Data sheet (MSDS).
- 17. <u>Venue</u>. Any dispute arising under this order not disposed of by agreement shall be decided by a court of competent jurisdiction in Cuyahoga County in the State of Ohio. Pending settlement on final decision of any dispute, Seller shall proceed diligently with the performance of this order in accordance with the City's direction. The Charter and Ordinance of the City of Cleveland shall govern.
- 18. <u>Tax.</u> Buyer is exempt from Federal and State taxes for tangible personal property. Sellers doing business with the Buyer may not be exempt from paying sales tax to their suppliers for materials to fulfill contractual obligations with the Buyer, nor shall any Seller be authorized to use the Buyer's Tax Exemption number in acquiring such materials, without the prior issuance of a signed Tax Exemption Certificate. A Tax Exemption Certificate is available upon written request.
- 19. Documentation. Seller shall clearly mark all documentation with the applicable valid PO number.
- 20. <u>Payment Terms.</u> Payment will be made in accordance with the terms on the face of this contract, or the Seller's invoice, whichever are more favorable to the City and payment date therefore shall be calculated from the receipt of invoice or receipt or final acceptance of the goods or services, whichever is later. All claims for money due or to become due from the City shall be subject to deduction or setoff by the City by reason of any counterclaim arising out of this or any other transaction with the Seller. The acceptance by the Seller of final payment shall operate as a full and complete release of the City. No payment for goods or services shall constitute acceptance of any defective or nonconforming goods or services by the city. Unless otherwise stated in the PO, the terms of payment shall be net 30 days from the receipt of a proper invoice. It shall be understood that the cash discount period, if any, to the City will date from receipt by the City of acceptable goods and invoice and not from date of invoice.
- 21. <u>Insurance</u>. Unless otherwise stated in the specifications, whenever labor is involved, the Seller shall procure and maintain insurance against claims for injuries to persons or damages to property, which may arise from or in connection with the services, materials, equipment and/or supplies provided to the City. The insurer(s) must be licensed for business in the State of Ohio and maintain an A.M.Best rating of no less than A: VII or be an insurer approved by the City. The Seller shall submit all required insurance certificates to the City before commencing work. The City is to be added to each policy as an additional insured. The Seller shall notify the City in writing at least 30 days before it cancels or reduces its insurance policy or coverage and immediately upon the Company's receipt of notice from the carrier of any cancellation or reduction of the coverage or policy. Seller must demonstrate the following minimum insurance coverage in accordance with the estimated value limits: 1) <u>Purchases less than \$50,000</u>: General Liability Insurance, with a \$500,000 combined single limit. 2) <u>Purchases \$50,000 and over:</u> General Liability Insurance with bodily injury and property damage limits of \$1,000,000 for each accident; OR \$1,000,000 combined single limits, including bodily injury and property damage. The above limits are the minimum acceptable and do not infer or place a limit on the liability of the Seller. The Seller's insurance shall be primary and any insurance or self-insurance maintained by the City shall be excess for the City and not contribute with the coverage maintained by the Seller.
- 22. <u>Workman's Compensation</u>: Whenever labor is involved, the Seller shall subscribe to and comply with the Workmen's Compensation Laws of the State of Ohio and pay such premiums as may be required there under and to save the City harmless from any and all liability arising from or under said act. He shall also furnish a copy of the official certificate or receipt showing the payments herein referred to before commencing any work.
- 23. Authority to Bind. All parties to this order agrees that the representatives named herein, including in all attachments, possess full and complete authority to bind said parties.
- 24. <u>Inspection and Acceptance</u>. No material received by the City pursuant to the purchase order issued under the terms and conditions of this bid document shall be deemed accepted until the City has had reasonable opportunity to inspect said material. All material which is discovered to be defective or which does not conform to any warranty of the Seller herein, upon initial inspection, or at any later time if the defects contained in the material were not reasonably ascertainable upon the initial inspection, may be returned at the Seller's expense for full credit or replacement. No goods returned as defective shall be replaced without written authorization from the Commissioner of Purchases and Supplies. Such return shall in no way affect the City's discount privileges. Such right to return, offered to the City arising from the City's receipt of defective goods, shall not exclude any other legal, equitable or contractual remedies the City may have therefore.
- 25. <u>Non-appropriation of Funds</u>. As with any other public entity, an Agreement, Contract, or issuance of Purchase Order by the City is contingent upon the legal availability of funding and the allocation of said funds. The City reserves the right to cancel any ongoing Agreement, Contract, or Purchase Order immediately, by giving written notice to the Seller, in the case of a failure by the appropriating body to appropriate funds or funding for the specific project, commodity or service.
- 26. Equal Opportunity. This Agreement is a "contract", and the Seller is a "contractor" within the meaning of Chapter 187 of the Codified Ordinances of Cleveland, Ohio 1976. During the term of this Purchase Order, the Seller shall comply with all terms, conditions and requirements imposed on a "contractor" in the Equal Opportunity Clause, Section 187.22(b) C.O., and herein made a part of this Agreement by reference. A complete copy of the Equal Opportunity Clause is available at the City of Cleveland website.

Subject: Submission of NORTHERN IRELAND FAIR EMPLOYMENT PRACTICES DISCLOSURE

Each bidder and/or appropriate parties should complete the <u>DISCLOSURE</u> and submit it with the bid, if possible. If not submitted with the bid, it must be completed and submitted to the Commissioner of Purchases and Supplies prior to any contract being awarded by the City. If a bidder or appropriate parties fail to complete and submit it, they shall not be eligible for a contract award.

NORTHERN IRELAND FAIR EMPLOYMENT PRACTICES DISCLOSURE

INSTRUCTIONS: Pursuant to Codified Ordinance Sec. 181.36, the information requested on this page must be supplied by all Contractors and any Subcontractors having more than a fifty percent (50%) interest in the proposed contract prior to any contract being awarded by the City of Cleveland. Any Contractor or Subcontractor who is deemed to have made a false statement shall be declared to have acted in default of its contract and shall be subject to the remedies for default contained in its contract. For failure to cure such a default, the Contractor or Subcontractor shall be automatically excluded from bidding for the supply of any goods or services for use by the City for a period of two years.

CHECK WHICHEVER IS APPLICABLE:

A. () The undersigned or any controlling shareholder,* subsidiary, or parent corporation of the undersigned is NOT ENGAGED IN ANY BUSINESS OR TRADING FOR PROFIT IN NORTHERN IRELAND. (If paragraph A. is checked, proceed to the signature line.)

B. () The undersigned or any controlling shareholder,* subsidiary, or parent corporation IS ENGAGED IN ANY BUSINESS OR TRADING FOR PROFIT IN NORTHERN IRELAND. (If paragraph B. is checked, please either check the stipulation contained in paragraph C. or attach documentation that shows that the undersigned has complied with the stipulation contained in paragraph C.

C. () The undersigned and all enterprises identified in paragraph B. are TAKING LAWFUL AND GOOD FAITH STEPS TO ENGAGE IN FAIR EMPLOYMENT PRACTICES WHICH ARE RELEVANT TO THE STANDARDS EMBODIED IN THE "MacBRIDE PRINCIPALS FOR FAIR EMPLOYMENT IN NORTHERN IRELAND." A copy of the MacBride Principles can be obtained from the Office of the Commissioner of Purchases and Supplies. In lieu of checking this paragraph, the undersigned must attach documentation which the undersigned believes shows compliance with the stipulation contained in this paragraph C.

Name	of Contractor or Subcontractor
By: _	
Title:	

*"Controlling shareholder" means any shareholder owning more than fifty percent (50%) of the stock in the corporation or more than twenty-five percent (25%) of the stock in the corporation if no other shareholder owns a larger share of stock in the corporation.



WAGE THEFT AND PAYROLL FRAUD DISCLOSURE

SUMMARY:

Bidders on certain City contracts, recipients of Assistance, and any of their prospective subcontractors must disclose any wage theft or payroll fraud violations over the last three years. Unless they receive a waiver from the City's Fair Wage Employment Board, violators are placed on the City's Adverse Determination List, which prevents them from entering into new contracts with or receiving Assistance from the City. This disclosure requirement and the waiver process are set forth in Chapter 190 of the Codified Ordinances of Cleveland, Ohio, 1976 ("Chapter 190").

INSTRUCTIONS:

Pursuant to Chapter 190, the information requested on this document must be provided by any person or entity bidding on or making a proposal for a Construction or Improvement Contract or a Service Contract, or applying for Assistance, and any of their prospective subcontractors.

Any person or entity that is deemed to have made a false statement shall be declared to have acted in default of its contract and shall be subject to the remedies for default contained in its contract.

DEFINITIONS:

"Adverse Determination" means a final action or adjudication that the person or entity in question has committed Wage Theft or Payroll Fraud and is further defined in Chapter 190.

"Assistance" means any form of City financial assistance, except for financial assistance provided for the development, rehabilitation or other means of providing residential housing. Assistance includes but is not limited to: grants; economic development loans; tax credits, incentives and abatements; subsidies; and bonds. Assistance does not include financial assistance which is received from another government or other entity with the City acting only as a conduit or fiscal agent for the funds, where the City exercises no control over the identity of any recipient or of the terms of the contract. Community Development Block Grant Funds are not considered conduit funds and, to the extent they otherwise qualify, are included as Assistance.

"Construction or Improvement Contract" means any contract entered into pursuant to Chapter 167 or Chapter 185 of the Codified Ordinances.

"Payroll Fraud" means concealing an entity's true payroll tax liability or other financial liability to a government agency from government licensing, regulatory or taxing agencies through misclassification of employees, failure to report or underreported



payment of wages, or executing a cash transaction while failing to maintain proper records of reporting and withholding.

"Service Contract" means any contract or subcontract between a person, business or corporation and the City of Cleveland that primarily involves the furnishing of services to the City (as opposed to the purchase of goods or other property or the leasing of property), and shall be limited to the following categories of services: food service, janitorial, security services, parking lot attendants, home health care, health care aides, waste management, automotive repair services, landscaping, towing contracts, building and maintenance services, carpentry, clerical services, urban forestry, housekeeping, street maintenance and repair, and sidewalk maintenance and repair. This includes services performed on City-owned premises including the following City-owned locations: airports, parking lots, municipal parks, recreational facilities, and City-owned buildings. Contracts that are primarily for the purchase of goods or other property are not considered Service Contracts.

"Wage Theft" means a violation of the Ohio Prompt Pay Statute, RC 4113.15; the Ohio Minimum Fair Wage Standards Act, RC Chapter 4111; Oh. Const. Art. II, Sec. 34a; RC Chapters 4109 or 4115; RC 4113.17, 4113.18, 4113.52 or 4113.61; or a violation of any substantially equivalent federal or state law; as any of these laws may be amended or superseded.

CHECK WHICHEVER IS APPLICABLE:

- (A)() The undersigned person or entity HAS NOT had any Adverse Determinations within the last three (3) years.
- (B) () The undersigned person or entity HAS had any Adverse Determinations within the last three (3) years.

If (B) is checked, then in an attachment(s) to this form, please disclose all Adverse Determinations within the last three (3) years.

Name of Person or Entity:

Signature: _____ Printed Name of Signatory: _____ Title of Signatory: _____

Date:

ForkLift Specs.

(1)Mast 03-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation.

Mast Specifications:

• Maximum Fork Height - 187.0"

• Overall Lowered Height - 89.2"

• Over Head Guard Height - 85.50"

• Free Lift - 41.2" with standard Load Backrest

Lifting Capacity Base Model Capacity - 6,000 lbs. @24" load center

Actual Capacity, based on quoted specifications - 5,750 lbs. @24" load center to

187.0" MFH

Tilt 6 degrees forward and 6 degrees backwards

Carriage ITA Hook Type 42" Carriage

Forks 48" x 5" x 1.8" - Class III

Load Backrest 48" High Load Backrest

Attachments Cascade 42" Integral Side shifting Fork Positioner (Maximum 96" Forks- longer than 96", consult Cascade)

Speeds Travel Speed: 11.50 mph Lift Speed: 102 fpm

Engine 2.2L 4Y-US Industrial LP Engine

136 cubic inch displacement, 4-cylinder, overhead valve (OHV)

Net Torque Rating: 112 @ 1800 rpm SAE ft-lb

Net Horsepower Rating: 51 @ 2570 rpm SAE HP

Transmission Automatic Transmission

Steering Load Sensing Hydrostatic Power Steering with Tilt Steering Column

Wheels and Tires Front Tires: 28x9-15-12PR (Pneumatic)

Rear Tires: 6.50-10-10PR (Pneumatic)

Additional Equipment Included

- Int SSFP w 3&4 funct. hose
- UL Approved Model Type "LP" (tank not included)
- Synchronized Steering
- Steel Cabin (With Doors)
- Rear View Mirrors (Left & Right Sides)
- Adjustable Volume Back-up Alarm (Smart Alarm)
- Seatbelt Interlock
- Fire Extinguisher
- Programmable Security Lock
- LED Strobe Light (Amber)
- LED Front Combination Lights
- LED Rear Combination Lights
- Blue Light (Back ON/OFF)
- Key On / Key Off Lights
- FWD Blue Light (Key ON/OFF)
- Red Zone Light
- Front Solid Pneumatic Tires Including Quick Heel Style Rims
- Rear Solid Pneumatic Tires Including Quick Heel Style Rim

All quantities are approximate and the order if any, shall not exceed \$46,464.00 or one (1) year whichever occurs first.